16961 Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 21 S

S 28	S 27
S 33	S 34

R 4 W
1958

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears S. 45° W., 34 lks. dist., no marks visible.

A sawed fir stump, 42 ins. diam., bears N. 46° W., 22 1/2 lks. dist., with scribe mark B visible on opened blaze. (Record, N. 40° W., 20 lks.)

and bearing trees mkd. by Byron

A fir, 6 ins. diam., bears N. 70° E., 31 1/2 lks. dist., with healed double blaze.

A fir, 18 ins. diam., bears S. 49° E., 83 lks. dist., with healed double blaze.

A fir, 21 ins. diam., bears S. 71° W., 11 1/2 lks. dist., with healed double blaze.

A fir, 13 ins. diam., bears N. 61 1/2° W., 43 lks. dist., with healed double blaze.

N. 0° 51' E., bet. secs. 27 and 28.

Descend 115 ft. over NE. slope, through heavy timber and dense undergrowth.

5.50 Creek, 2 lks. wide, course S. 60° E.; desc. 60 ft. over broken NE. slope.

9.30 Bear Creek, 10 lks. wide, course N. 60° W.; asc. 125 ft. over SW. slope.

12.15 Dirt road, 25 lks. wide, bears N. 60° W. and S. 60° E.

15.60 Gravelled driveway, 20 lks. wide, bears NW. and SW., in curve.

20.04 The S 1/16 sec. cor. of secs. 27 and 28, established by William A. Eimstad, Registered Land Surveyor, No. 377, in 1979, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Eimstad

A fir, 18 ins. diam., bears N. 29 1/4° E., 16 lks. dist., with scribe marks S 1/16 S27 BT visible on open blaze.

A fir, 11 ins. diam., bears S. 68 3/4° W., 20 1/2 lks. dist., with scribe marks S 1/16 S28 BT visible on open blaze.

and bearing trees mkd. by person(s) unknown.