

County Surveyor's Record, Douglas County, Oregon

16962

Dependent Resurvey, Portion of Subdivisional Lines,
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 45 ins. diam., bears N. 25° E., 44 1/2 lks. dist., with fragmentary scribe marks visible on bark blaze.

A fir, 40 ins. diam., bears N. 34 3/4° W., 54 1/2 lks. dist., with fragmentary scribe marks visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long., 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

S 1/16
S 28 | S 27
1980

N. 0° 54' E., beginning new measurement.

Ascend 245 ft. over SW. slope.

9.50

Spur, slopes S. 60° W.; desc. 55 ft. over NW. slope.

20.04

The 1/4 sec. cor. of secs. 27 and 28, perpetuated and recorded by William A. Eimstad, Registered Land Surveyor, No. 377, in 1979, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears S. 81° E., 14 lks. dist., with illegible scribe marks visible on decayed blaze.

and bearing trees mkd. by Eimstad

A fir, 13 ins. diam., bears N. 58 1/2° E., 60 lks. dist., with scribe marks 1/4 S27 BT visible on open blaze.

A cedar, 8 ins. diam., bears N. 9 3/4° W., 31 lks. dist., with scribe marks 1/4 S28 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 21 S R 4 W
1/4
S 28 | S 27
1980

*FOOK 7/95 BY ROBERTS
M122-AS*

N. 0° 41' E., beginning new measurement.

Descend 45 ft. over broken NW. slope.

4.65

Creek, 5 lks. wide, course S. 65° W.; asc. 145 ft. over SW. slope.