

# County Surveyor's Record, Douglas County, Oregon

16968

T. 22 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, Township 22 South, Range 4 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The north boundary and a portion of the subdivisional lines were surveyed by Harvey Gordon and Charles T. Gardner in 1855.

A portion of the subdivisional lines was surveyed by William P. Wright in 1884.

The survey of the subdivisional lines was completed by Oscar F. Thiel in 1901.

A portion of the subdivisional lines was resurveyed by Donald R. Beck in 1963.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1026, Oregon, dated June 5, 1980.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines were measured twice.

The geographic position of the 1/4 section corner of sections 2 and 3, as scaled from the United States Geological Survey quadrangle map, "ANLAUF, OREGON", prepared in 1954, is as follows:

Latitude 43° 41.1' N. Longitude 123° 08.8' W.

The mean magnetic declination is 18° 45' E.

Dependent Resurvey of a  
Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

(Restoring the survey by William P. Wright,  
U.S. Deputy Surveyor, in 1884 and the survey  
by Oscar F. Thiel, U.S. Deputy Surveyor, in 1901)

Beginning at the 1/4 sec. cor. of secs. 2 and 3, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.