

# County Surveyor's Record, Douglas County, Oregon

16969

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 22 S    R 4 W  
1/4 S 3 | S 2  
1962

from which the only remaining original bearing tree

A cedar, 36 ins. diam., bears N. 7° E., 5 lks.  
dist., with illegible scribe marks visible  
on opened blaze.

and a bearing tree mkd. by Godfrey

A cedar, 13 ins. diam., bears S. 88° W., 55 lks.  
dist., with healed blaze.

N. 1° 11' W., bet. secs. 2 and 3, marking and blazing the true line.

Descend 45 ft. over broken NE. slope, through heavy timber and dense undergrowth.

2.65    Creek, 2 lks. wide, course NE.; desc. 15 ft. over broken NE. slope.

9.75    Spur, slopes NE.; desc. 80 ft. over NE. slope.

12.45    Ravine, drains N. 60° E.; desc. 85 ft. over NE. slope.

15.90    Creek, 5 lks. wide, course N. 30° W.; asc. 15 ft. over SW. slope.

17.40    Top of ascent, slopes W.; desc. 10 ft. over NW. slope.

19.90    Point for the N 1/16 sec. cor. of secs. 2 and 3.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

N 1/16  
S 3 | S 2  
1981

from which

A fir, 14 ins. diam., bears S. 25° E., 5 lks.  
dist., mkd. N 1/16 S2 BT.

A fir, 12 ins. diam., bears N. 24° W., 24 lks.  
dist., mkd. N 1/16 S3 BT.

Descend 50 ft. over NW. slope.

29.30    Creek, 3 lks. wide, course W.; asc. 70 ft. over broken SW. slope.

39.26    Intersect the S. bdy. of sec. 35, T. 21 S., R. 4 W.

True point for the closing cor. of secs. 2 and 3.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.