

County Surveyor's Record, Douglas County, Oregon

16975

T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 32 South, range 6 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

The east and north boundaries of the township and a portion of the subdivisional lines were surveyed by Wells Lake and George W. Hyde, in 1855.

The survey of the subdivisional lines was completed by William H. Byars, in 1881.

A portion of the subdivisional lines was resurveyed and section 15 was subdivided by Rollin D. Aanrud, in 1966-67.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated June 11, 1980, for Group Number 1018, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming closures were measured twice.

The geographic position of the corner of sections 13, 14, 23, and 24, as scaled from the Canyonville, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude $42^{\circ} 47.0' N.$ Longitude $123^{\circ} 22.0' W.$
The mean magnetic declination is $20^{\circ} E.$

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the survey by Wells Lake and George W. Hyde,
U. S. Deputy Surveyors, in 1855,
and the survey by William H. Byars,
U. S. Deputy Surveyor, in 1881)

Beginning at the cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of an original bearing tree:

A decayed madrone stump, size indeterminate, bears
S. $10^{\circ} E.$, 16 lks. dist., no marks visible.