

County Surveyor's Record, Douglas County, Oregon

16376

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

and bearing trees mkd. by Wenderoth

A madrone, 8 ins. diam., bears N. 30° E., 21 lks. dist., with scribe marks CS BT visible on partially healed blaze.

A madrone, 11 ins. diam., bears S. 60° W., 30 1/2 lks. dist., with healed blaze.

A chinquapin, 12 ins. diam., bears N. 53° W., 20 lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over iron pipe, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 32 S	R 6 W
S 14	S 13
S 23	S 24
1980	

from which a new bearing tree

A madrone, 8 ins. diam., bears S. 29 1/2° E., 45 lks. dist., mkd. T32S R6W S24 BT.

N. 0° 13' E., bet. secs. 13 and 14, marking and blazing the true line.

Ascend 75 ft. over SE. slope, through heavy timber and dense undergrowth.

7.00 Spur ridge, bears NE. and SW.; desc. 365 ft. over NW. slope.

30.55 Bear Creek, 8 lks. wide, course S. 55° W.; asc. 120 ft. over SE. slope.

39.25 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S	R 6 W
1/4	
S 14	S 13
1980	

from which

A madrone, 8 ins. diam., bears N. 57 1/2° E., 11 lks. dist., mkd. 1/4 S13 BT.

A fir, 7 ins. diam., bears S. 38 1/2° W., 76 lks. dist., mkd. 1/4 S14 BT.

Ascend 200 ft. over broken SE. slope.

51.30 Spur, slopes E.; desc. 25 ft. over NE. slope.

54.30 Creek, 1 lk. wide, course S. 60° E.; asc. 125 ft. over SE. slope.