

County Surveyor's Record, Douglas County, Oregon

16977

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

78.50

The cor. of secs. 11, 12, 13, and 14, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 55° E., 50 lks. dist., with a down fir alongside, 40 ins. diam., no marks visible.

A sawed fir stump, 44 ins. diam., bears S. 50° E., 76 lks. dist., no marks visible.

A root hole, bears S. 78° W., 32 lks. dist.

A root hole, bears N. 53° W., 40 lks. dist., with a down fir alongside, 38 ins. diam., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T	32	S	R	6	W
	S	11		S	12
	S	14		S	13
1980					

from which new bearing trees

A fir, 15 ins. diam., bears N. 52° E., 32 lks. dist., mkd. T32S R6W S12 BT.

A fir, 11 ins. diam., bears S. 56 3/4° E., 52 lks. dist., mkd. T32S R6W S13 BT.

A fir, 8 ins. diam., bears S. 16° W., 72 lks. dist., mkd. T32S R6W S14 BT.

A fir, 7 ins. diam., bears N. 50 3/4° W., 28 lks. dist., mkd. T32S R6W S11 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrone, chinquapin, and alder; undergrowth, poison oak, manzanita, arrowwood, hazel, vine maple, salal, Oregon grape, and young timber.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., perpetuated and recorded by the County Surveyors Office, in 1959, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

R	S	12		S	7	R
6	S	13		S	18	5
W	T 32 S				W	
1959						

from which the remains of the original bearing trees

A madrone, 15 ins. diam., bears N. 34° E., 47 lks. dist., with illegible scribe marks visible on weathered and partially healed blaze.

A cedar, 16 ins. diam., bears S. 24° E., 34 lks. dist., with burned blaze, no marks visible.