

# County Surveyor's Record, Douglas County, Oregon

16378

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 6 W., Willamette Meridian, Oregon

**CHAINS**

A decayed fir stump, size indeterminate, bears S. 11° W., 48 lks. dist., with chaining notch visible on burned blaze.

and bearing trees mkd. by the County Surveyors Office

A fir, 17 ins. diam., bears N. 32° E., 58 1/2 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 59 3/4° E., 78 lks. dist., with healed blaze.

A fir, 48 ins. diam., bears South, 15 lks. dist., with scribe marks BT visible on partially healed blaze.

A madrone, 7 ins. diam., bears N. 52° W., 37 lks. dist., with healed blaze.

S. 88° 55' W., bet. secs. 12 and 13.

Descend 85 ft. over SW. slope, through heavy timber and moderate undergrowth.

2.30 Creek, 3 lks. wide, course S.; asc. 315 ft. over SE. slope.

24.30 Spur, slopes S.; desc. 175 ft. over SW. slope.

31.10 Bottom of descent, slopes S.; asc. 160 ft. over SE. slope.

40.21 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S    R 6 W  
1/4  $\frac{S 12}{S 13}$   
1980

from which

A cedar, 9 ins. diam., bears N. 77 3/4° E., 34 1/2 lks. dist., mkd. 1/4 S12 BT.

A fir, 15 ins. diam., bears S. 22° W., 59 lks. dist., mkd. 1/4 S13 BT.

Ascend 5 ft. over SE. slope.

41.50 Bear Ridge, bears N. and S.; desc. 50 ft. over W. slope.

42.90 Gravelled road, 30 lks. wide, bears N. 15° W. and S. 15° E.

45.80 Ravine, drains SW.; asc. 70 ft. over SE. slope.

50.90 Spur, slopes SW.; desc. 160 ft. over W. slope.

56.50 Ravine, drains SW.; desc. 345 ft. over W. slope.

67.95 Bear Creek, 10 lks. wide, course S. 10° E.; asc. 90 ft. over SE. slope.