

County Surveyor's Record, Douglas County, Oregon

16380

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which

- A fir, 10 ins. diam., bears N. 32° E., 29 lks. dist., mkd. T32S R6W S1 BT.
- A fir, 6 ins. diam., bears S. 40° E., 40 1/2 lks. dist., mkd. T32S R6W S12 BT.
- A fir, 8 ins. diam., bears S. 16 1/2° W., 16 1/2 lks. dist., mkd. T32S R6W S11 BT.
- A fir, 6 ins. diam., bears N. 88 1/4° W., 46 lks. dist., mkd. T32S R6W S2 BT.

Land, mountainous.
Soil, rocky clay.
Timber, fir, pine, cedar, oak, madrone, chinquapin, alder, and dogwood; undergrowth, poison oak, manzanita, arrowwood, hazel, vine maple, huckleberry, salal, Oregon grape, and young timber.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., perpetuated and recorded by Louis W. Amort, Registered Engineer No. 2311, in 1960, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

ORE ST BD OF FORESTRY

T 32 S
R 6 W R 5 W
S 1 | S 6
S 12 | S 7
1960
RE 2311

from which the remains of the original bearing trees

- A root hole, bears N. 24° E., 59 lks. dist., with a down and decayed cedar alongside, size indeterminate, no marks visible.
- A root hole, bears S. 24° W., 56 lks. dist., with a down cedar alongside, 8 ins. diam., no marks visible.
- A root hole, bears N. 36° W., 39 lks. dist., with a down and decayed cedar alongside, size indeterminate, with illegible scribe marks visible on overgrowth.

and the remains of bearing trees mkd. by Amort

- A root hole, bears N. 16 1/2° E., 100 lks. dist., with a down cedar alongside, 14 ins. diam., with illegible scribe marks visible on partially healed blaze.
- A fir, 42 ins. diam., bears S. 28° E., 18 lks. dist., with scribe marks T32S R5W S7 BT visible on partially healed blaze.
- A cedar, 32 ins. diam., bears S. 34° W., 71 lks. dist., with illegible scribe marks visible on partially healed blaze.