

County Surveyor's Record, Douglas County, Oregon

16984

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS									
	Ascend 75 ft. over SE. slope, through heavy timber and dense undergrowth.								
4.25	Buck Ridge, bears N. 40° E. and S. 40° W., also dirt road, 15 lks. wide, bears same as ridge; desc. 780 ft. over W. slope.								
27.25	Lawson Creek, 7 lks. wide, course S. 50° W.; asc. 255 ft. over broken SE. slope.								
39.76	Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T 32 S</td><td style="padding: 0 10px;">R 6 W</td></tr> <tr><td style="padding: 0 10px;">1/4</td><td style="padding: 0 10px;">S 2</td></tr> <tr><td style="padding: 0 10px;"></td><td style="padding: 0 10px;">S 11</td></tr> <tr><td colspan="2" style="padding: 0 10px;">1980</td></tr> </table>	T 32 S	R 6 W	1/4	S 2		S 11	1980	
T 32 S	R 6 W								
1/4	S 2								
	S 11								
1980									
	from which								
	A fir, 6 ins. diam., bears N. 27 1/2° E., 59 lks. dist., mkd. 1/4 S2 BT.								
	A fir, 6 ins. diam., bears S. 24° E., 27 lks. dist., mkd. 1/4 S11 BT.								
	Ascend 195 ft. over broken SE. slope, changing to S. slope.								
59.45	Ravine, drains SE.; asc. 340 ft. over E. slope.								
68.50	Top of rocky bluff, 30 ft. high, bears N. and S.; asc. 355 ft. over E. slope.								
77.75	Ridge, bears N. and S.; desc. 45 ft. over W. slope.								
79.52	The cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1959, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.								
	<p style="margin: 0;">COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T 32 S</td><td style="padding: 0 10px;">R 6 W</td></tr> <tr><td style="padding: 0 10px;">S 3</td><td style="padding: 0 10px;">S 2</td></tr> <tr><td style="padding: 0 10px;">S 10</td><td style="padding: 0 10px;">S 11</td></tr> <tr><td colspan="2" style="padding: 0 10px;">1959</td></tr> </table>	T 32 S	R 6 W	S 3	S 2	S 10	S 11	1959	
T 32 S	R 6 W								
S 3	S 2								
S 10	S 11								
1959									
	from which the remains of the original bearing trees								
	A decayed fir stump, size indeterminate, bears N. 35° E., 19 lks. dist., no marks visible.								
	A fir, 42 ins. diam., bears S. 65° E., 28 lks. dist., with healed blaze.								
	A sawed fir stump, 40 ins. diam., bears S. 60° W., 9 lks. dist., with healed blaze.								
	and the remains of bearing trees mkd. by Byron								
	A fir snag, 20 ins. diam., bears N. 37° E., 134 lks. dist., with healed blaze.								