

County Surveyor's Record, Douglas County, Oregon

16988

Dependent Resurvey, Portion of Subdivisional Lines
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 29 S	R 8 W
S 11	S 12
S 14	S 13
1924	

from which the remains of an original bearing tree

A root hole bears N. 54° W., 31 lks. dist., with a down pine alongside, size indeterminate, no marks visible. (Original record, N. 50° W.)

and remains of bearing trees mkd. by Mensch

A root hole, bears N. 64° E., 18 lks. dist., with down fir alongside, 10 ins. diam., with scribe marks T29S R8W S12 BT visible on open blaze.

A fir, 18 ins. diam., bears S. 82° E., 20 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears S. 66° W., 7 lks. dist., with healed blaze.

A fir snag, 10 ins. diam., bears N. 33° W., 14 lks. dist., with healed blaze.

and remains of bearing trees mkd. by John M. Powell, Deputy Douglas County Surveyor in 1966

A sawed fir stump, 17 ins. diam., bears N. 41° E., 25 lks. dist., with scribe marks 29 BT visible on open double blaze.

A root hole bears N. 72° W., 23 lks. dist. with a down fir alongside, 10 ins. diam., with illegible scribe marks visible on partially healed double blaze.

and bearing trees mkd. by Larry E. Monrean, Deputy Douglas County Surveyor in 1977

A madrone, 40 ins. diam., bears N. 76 1/4° E., 76 lks. dist., with scribe marks T29S R8W S12 CS BT visible on open double blaze.

A fir, 17 ins. diam., bears N. 45° W., 97 lks. dist., with illegible scribe marks visible on pitch-covered double blaze.

N. 0° 12' W., bet. secs. 11 and 21, marking and blazing the true line.

Ascend 415 ft. over SE. slope, along timber cut line, timber to west, clear-cut to east.

20.03

Point for the S 1/16 sec. cor. of secs. 11 and 12.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16	
S 11	S 12
1980	

from which