

# County Surveyor's Record, Douglas County, Oregon

16989

Dependent Resurvey, Portion of Subdivisional Lines  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

A cedar, 5 ins. diam., bears S. 26° E., 119 lks. dist., marked X BT.

A fir, 42 ins. diam., bears S. 6° W., 29 lks. dist., marked S 1/16 S11 BT.

Corner is located in timber corner, edge bears S. and W., timber to SW.

Ascend 5 ft. over SE. slope.

20.35 Ridge bears N. 80° E. and S. 80° W.; desc. 330 ft. over broken NE. slope.

34.20 Ravine, drains W.; asc. 10 ft. over SW. slope.

35.70 Gravelled road, 20 lks. wide, bears N. 20° W. and S. 45° E.

40.06 The 1/4 sec. cor. of secs. 11 and 12, perpetuated and recorded by John M. Powell, Deputy Douglas County Surveyor in 1966, further perpetuated and recorded by Gary L. Langlitz, Deputy Douglas County Surveyor in 1978, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

1	T 29 S	R 8 W
/		
4	S 11	S 12
	1966	

from which the remains of the original bearing trees

A laurel stump, 14 ins. diam., bears S. 89° E., 69 lks. dist., with scribe mark 4 visible on opened blaze. (Record, 68 lks.)

A fir stump, 45 ins. diam., bears N. 6° W., 30 lks. dist., no marks visible. (Record, N. 3° W.)

and bearing trees marked by Powell

A root hole, bears S. 49° E., 22 lks. dist., with down madrone alongside, 10 ins. diam., with scribe marks 1/4 S12 CS BT visible on open double blaze.

A hemlock stump, 10 ins. diam., bears N. 73° W., 14 1/2 lks. dist., with healed double blaze.

and bearing trees marked by Langlitz

A fir, 8 ins. diam., bears S. 44 1/2° E., 52 lks. dist., with scribe marks 1/4 S12 CS BT visible on open double blaze.

A grand fir, 8 ins. diam., bears S. 2 3/4° W., 98 lks. dist., with scribe marks 1/4 S11 CS BT visible on open blaze.