

County Surveyor's Record, Douglas County, Oregon

16991

Dependent Resurvey, Portion of Subdivisional Lines
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- N. 0° 27' W., beginning new measurement
Ascend 25 ft. over SE. slope.
- 2.20 Top of ascent, slopes N. 70° E.; desc. 35 ft. over NE. slope.
- 6.10 Ravine, drains S. 50° E.; asc. 155 ft. over SE. slope, changing to SW. slope.
- 6.80 Dirt road, 15 lks. wide, bears N. 60° W., and S. 60° E.
- 20.06 The 1/4 sec. cor. of secs. 14 and 15, perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor in 1958, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

1/4
S | S
15 | 14
T 29 S | R 8 W
1958

from which the remains of an original bearing tree

A root hole, bears N. 68° W., 94 lks. dist., with a down oak alongside, 24 ins. diam., no marks visible.

and bearing trees mkd. by Byron

A fir, 19 ins. diam., bears N. 73 3/4° E., 16 1/2 lks. dist., with healed blaze.

A fir, 26 ins. diam., bears N. 63° W., 18 1/2 lks. dist., with healed double blaze.
(Record, N. 58 1/4° W.)

and a bearing tree described in the 1973-76 resurvey as not being of record

A fir, 25 ins. diam., bears S. 74 3/4° W., 41 lks. dist., with healed blaze.

- N. 0° 08' E., beginning new measurement.
Ascend 95 ft. over broken SW. slope, changing to SE.
- 10.60 Spur, slopes E.; desc. 70 ft. over NE. slope.
- 19.80 Creek, 1 lk. wide, course S. 80° E.; asc. 30 ft. over SE. slope.
- 20.11 Point for the N 1/16 sec. cor. of secs. 14 and 15.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 15 | S 14
1982

Fd. BC and 2 BTs
R. Quimby 2/2008
C.S. File 65/63-9