

# County Surveyor's Record, Douglas County, Oregon

16994

Dependent Resurvey, Portion of Subdivisional Lines  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

Descend 110 ft. over NW. slope.

27.90 Ravine, drains S. 85° W.; asc. 40 ft. over SW. slope.

36.00 Spur, slopes NW.; desc. 195 ft. over NW. slope.

39.96 The 1/4 sec. cor. of secs. 10 and 11, perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1958, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

1/4 S 10 | S 11  
1958

from which the remains of an original bearing tree

A fir snag, 52 ins. diam., bears N. 38° W., 51 lks. dist., with scribe mark B visible on opened blaze.

and a bearing tree mkd. by Byron

A fir, 18 ins. diam., bears S. 76° W., 93 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 8 ins. diam., bears N. 25 1/2° E., 7 lks. dist., mkd. 1/4 S11 BT.

Land, mountainous.  
Soil, rocky cly.  
Timber, fir, yew pine, hemlock, ash, alder, oak, maple, and cedar; undergrowth, poison oak, Oregon grape, ferns, arrowwood, vine maple, elderberry, thimbleberry, salmonberry, blackberry, huckleberry, hazel, wild rose, and young timber.

From the cor. of secs. 14, 15, 22, and 23.

S. 89° 43' W., bet. secs. 15 and 22.

Descend 95 ft. over NW. slope, through heavy timber and dense undergrowth.

4.85 Gravelled road, 20 lks. wide, bears N. 30° E. and S. 30° W.

8.45 Berry Creek, 20 lks. wide, course N. 35° E.; asc. 160 ft. over SE. slope.

19.79 The E 1/16 sec. cor. of secs. 15 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

E 1/16  $\frac{S 15}{S 22}$   
1976

FD BC AND 2 BTS  
RON QUIMBY  
12/2007  
C.S. 65/63-6

from which bearing trees mkd. by Jelley, Akin, and Shaner

A fir, 9 ins. diam., bears N. 78° E., 51 lks. dist., with scribe marks E 1/16 S15 BT visible on open blaze. (Record, N. 77° E.)