

# County Surveyor's Record, Douglas County, Oregon

16995

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 15 ins. diam., bears S. 66° E., 39 1/2 lks. dist., with healed blaze.

S. 89° 43' W., beginning new measurement.

Ascend 315 ft. over SE. slope.

14.65 Spur, slopes S.; desc. 60 ft. over SW. slope.

19.98 The 1/4 sec. cor. of secs. 15 and 22, perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1958, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S    R 8 W  
1/4      S 15  
          S 22

1958

from which the remains of the original bearing trees

A black oak, 18 ins. diam., bears N. 30° E., 70 lks. dist., with scribe marks BT visible on open blaze.

A root hole, bears S. 7° W., 135 lks. dist., with down pine alongside, 32 ins. diam., no marks visible.

and bearing trees mkd. by Byron

A fir, 8 ins. diam., bears N. 1/2° E., 34 lks. dist., with healed double blaze. (Rec., N. 2° E.)

A cedar, 16 ins. diam., bears S. 60 3/4° W., 33 1/2 lks. dist., with healed double blaze. (Record, fir)

From the cor. of secs. 15, 16, 21, and 22, perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1958, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S    R 8 W  
S 16    |    S 15  
-----  
S 21    |    S 22

1958

from which the remains of two original bearing trees

A madrone, 30 ins. diam., bears N. 70° E., 46 lks. dist., with healed blaze.

A sawed fir stump, 65 ins. diam., bears S. 8° E., 12 lks. dist., no marks visible. (Record, 10 lks.)

and bearing trees mkd. by Byron