

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

16996

**CHAINS**

A fir snag, 17 ins. diam., bears N. 21° E.,  
103 lks. dist., with scribe marks T29S R8W  
S15 CS BT visible on open double blaze.

A cedar, 14 ins. diam., bears N. 82° E.,  
49 lks. dist., with healed double blaze.

A grand fir, 20 ins. diam., bears S. 33 1/2° E.,  
180 lks. dist., with healed double blaze.

and new bearing trees

A fir, 12 ins. diam., bears S. 17° W.,  
44 lks. dist., mkd. T29S R8W S21 BT.

A fir, 8 ins. diam., bears N. 18 1/2° W.,  
24 lks. dist., mkd. T29S R8W S16 BT.

N. 0° 15' W., bet. secs. 15 and 16.

Ascend 15 ft. over SW. slope, through heavy timber and  
dense undergrowth.

1.70 Top of ascent, slopes S. 30° W.; desc. 295 ft. over  
NW slope.

35.60 Creek, 2 lks. wide, course N. 50° E.; asc. 55 ft. over  
SE. slope.

40.10 Point for the 1/4 sec. cor. of secs. 15 and 16, at propor-  
tionate dist.; there is no remaining evidence of the  
original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in  
the ground, with brass cap mkd.

T 29 S R 8 W  
1/4  
S 16 | S 15  
1982

from which

A fir, 15 ins. diam., bears S. 85° E., 20 lks.  
dist., mkd. 1/4 S15 BT.

A fir, 14 ins. diam., bears N. 24 1/2° W., 30 lks.  
dist., mkd. 1/4 S16 BT.

Ascend 5 ft. over SE. slope.

40.60 Top of ascent, slopes E.; desc. 70 ft. over NE. slope

43.95 Ravine, drains E.; asc. 75 ft. over SE. slope.

49.90 Spur, slopes E.; desc. 50 ft. over NE. slope.

55.10 Creek, 5 lks. wide, course S. 50° E.; asc. 95 ft. over  
SW. slope.

55.90 Dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.

60.15 Point for the N 1/16 sec. cor. of secs. 15 and 16.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in  
the ground, with brass cap mkd.