

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Studivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

16998

CHAINS

From the cor. of secs. 10, 11, 14, 15.

S. 89° 42' W., bet. secs. 10 and 15.

Ascend 110 ft. over SE. slope, through heavy timber and dense undergrowth.

4.45 Spur, slopes S. 10° E.; desc. 25 ft. over SW. slope.

12.65 Head of ravine, drains S. 10° W.; asc. 65 ft. over SE. slope.

19.88 Point for the E 1/16 sec. cor. of secs. 10 and 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 10}{S\ 15}$
1980

from which

A fir, 12 ins. diam., bears N. 35 1/2° E., 77 lks. dist., mkd. E 1/16 S10 BT.

A fir, 20 ins. diam., bears S. 15° E., 32 1/2 lks. dist., mkd. E 1/16 S15 BT.

Ascend 390 ft. over SE. slope.

37.20 Ridge, bears N. 5° E. and S. 5° W.; desc. 20 ft. over W. slope.

39.76 Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 29 S R 8 W
1/4 $\frac{S\ 10}{S\ 15}$
1980

from which

A fir, 15 ins. diam., bears S. 1/2° W., 10 1/2 lks. dist., mkd. 1/4 S15 BT.

A fir, 16 ins. diam., bears N. 50° W., 37 lks. dist., mkd. 1/4 S10 BT.

Descend 340 ft. over W. slope.

79.52 The cor. of secs. 9, 10, 15, and 16.

Land, mountainous.

Soil, rocky clay.

Timber, fir, madrone, oak, hemlock, cedar, ash, pine, yew, and alder; undergrowth, poison oak, Oregon grape, vine maple, ferns, arrowwood, hazel, elderberry, thimbleberry, salmonberry, wild rose, manzanita, and young timber.