

County Surveyor's Record, Douglas County, Oregon

16999

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

N. 0° 03' E., bet. secs. 9 and 10.

Descend 5 ft. over NW. slope, through heavy timber and dense undergrowth.


0.50

Three wire power transmission line, bears N. and W.; continue along the W. edge of right-of-way clearing.

20.05

Point for the S 1/16 sec. cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 22 ins. diam., bears N. 77 1/2° E., 136 lks. dist., mkd. S 1/16 S10 BT.

A fir, 9 ins. diam., bears S. 47 1/2° W., 16 lks. dist., mkd. S 1/16 S9 BT.

Ascend 20 ft. over SW. slope.

35.65


Ridge, bears N. 85° W. and S. 85° E.; desc. 180 ft. over NE. slope.

40.10

The 1/4 sec. cor. of secs. 9 and 10, perpetuated and recorded by Arthur Boyer, Deputy Douglas County Surveyor, in 1939, and further perpetuated and recorded by John M. Powell, Deputy Douglas County Surveyor, in 1967, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

FD BC
3/22/67
MKT-22



from which the remains of an original bearing tree

A root hole, bears N. 1/2° W., 53 lks. dist., with down fir alongside, 55 ins. diam., with no marks visible.

and a bearing tree mkd. by Boyer

A hemlock, 33 ins. diam., bears N. 70 1/2° W., 84 1/2 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a bearing tree mkd. by Powell

A sawed cedar stump, 20 ins. diam., bears S. 37° E., 17 1/2 lks. dist., with healed blaze.

and an unrecorded bearing tree

A cedar, 17 ins. diam., bears N. 52° E., 216 lks. dist., with fragmentary scribe marks visible on open blaze.