

County Surveyor's Record, Douglas County, Oregon

17000

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

N. 0° 07' W., beginning new measurement.

Descend 285 ft. over NE. slope; continue along W. edge of power line right-of-way clearing.

11.65 Shields Creek, 5 lks. wide, course S. 80° E.; asc. 205 ft. over SW. slope.

13.70 Three-wire power transmission line bears N. 75° E. and S. 75° W.

15.20 State Highway No. 42, asphalt surface, 60 lks. wide, bears N. 75° E. and S. 75° W.

26.40 Spur, slopes S. 60° E.; desc. 20 ft. over NE. slope.

33.00 Ravine, drains S. 65° E.; asc. 65 ft. over SW. slope.

40.10 The cor. of secs. 3, 4, 9, and 10, perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1958, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S	R 8 W
S 4	S 3
S 9	S 10
1958	

FD. 9/26/86
 O.S.H.D.
 C.S. 123/9

from which the remains of two original bearing trees

A fir, 38 ins. diam., bears S. 60° W., 22 lks. dist., with fragmentary scribe marks visible on bark blaze. (Record, 24 lks.)

(Per OSWD)
 S.E.

A sawed fir stump, 40 ins. diam., bears N. 70° W., 13 lks. dist., with fragmentary scribe marks visible on bark blaze.

and bearing trees mkd. by Byron

A grand fir, 18 ins. diam., bears N. 61° E., 63 lks. dist., with healed blaze.

A grand fir, 15 ins. diam., bears S. 7 1/4° E., 40 1/2 lks. dist., with healed blaze.

A sawed fir stump, 28 ins. diam., bears N. 87 1/2° W., 12 lks. dist., with healed blaze.

Land, mountainous.
 Soil, rocky clay.
 Timber, fir, hemlock, cedar, maple, oak, myrtle, alder, chinquapin, yew, and madrone; undergrowth, salal, poison oak, rhododendron, vine maple, Oregon grape, hazel, ferns, and young timber.

From the cor. of secs. 9, 10, 15, and 16.

S. 89° 47' W., bet. secs. 9 and 16.