

County Surveyor's Record, Douglas County, Oregon

17001

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	Descend 75 ft. over SW. slope, along the S. edge of power line right-of-way clearing.
19.85	<p>Point for the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $E\ 1/16\ \frac{S\ 9}{S\ 16}$ <p>1980</p> </div> <p>from which</p> <p style="margin-left: 40px;">A cedar, 11 ins. diam., bears N. 76 1/2° W., 30 lks. dist., mkd. E 1/16 S9 BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 8 1/4° W., 21 1/2 lks. dist., mkd. E 1/16 S16 BT.</p> <p>Descend 130 ft. over SW. slope.</p>
39.70	<p>The 1/4 sec. cor. of secs. 9 and 16, perpetuated and recorded by Ben B. Irving, Deputy Douglas County Surveyor, in 1939, from original evidence no longer in existence, and further perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1958; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> $T\ 29\ S\ \quad R\ 8\ W$ $1/4\ \frac{S\ 9}{S\ 16}$ <p>1958</p> </div> <p>from which bearing trees mkd. by Irving</p> <p style="margin-left: 40px;">A sawed fir stump, 30 ins. diam., bears N. 48° E., 34 lks. dist., with no marks visible.</p> <p style="margin-left: 40px;">A sawed fir stump, 26 ins. diam., bears S. 76 1/4° W., 32 1/2 lks. dist., with fragmentary scribe marks visible on decayed blaze.</p> <p>and a bearing object and bearing tree described by Byron</p> <p style="margin-left: 40px;">A basalt stone outcrop, 4 x 2 x 2 ft. high, bears N. 25° E., 20 lks. dist., with XBO visible on SW. face.</p> <p style="margin-left: 40px;">A fir, 32 ins. diam., bears S. 34 1/2° E., 32 1/2 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 53' W., beginning new measurement.</p> <p>Descend 100 ft. over SW. slope.</p>
3.05	<p>State Highway No. 42, 50 lks. wide, bears N. and S.</p>
19.985	<p>Point for the W 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>