

# County Surveyor's Record, Douglas County, Oregon

17003

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS					
	<p>Land mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, maple, oak, myrtle, madrone, chinquapin, and alder,; undergrowth, salal, rhododendron, vine maple, Oregon grape, poison oak, fern, and grasses.</p>				
	<p>N. 0° 11' E., bet. secs. 8 and 9.</p> <p>Descend 5 ft. over N. slope, through heavy timber and dense undergrowth.</p>				
4.50	Top of ascent, slopes W.; desc. 165 ft. over NW slope.				
8.75	Creek, 10 lks. wide, course W.; asc. 155 ft. over SW. slope.				
18.15	Spur, slopes W.; desc. 10 ft. over NW. slope.				
19.80	Ravine, drains S. 45° W.; asc. 5 ft. over SW. slope.				
19.985	Point for the S 1/16 sec. cor. of secs. 8 and 9.				
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 1/16</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S 8</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">1980</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears N. 33 1/2° E., 16 lks. dist., mkd. S 1/16 S9 BT.</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears S. 72 1/2° W., 8 1/2 lks. dist., mkd. S 1/16 S8 BT.</p> <p>Ascend 50 ft. over SW. slope.</p>	S 8	S 9	1980	
S 8	S 9				
1980					
24.45	Spur, slopes W.; desc. 55 ft. over NW. slope.				
28.50	Ravine, drains S. 50° W.; asc. 60 ft. over SW. slope.				
29.80	Spur, slopes S. 50° W.; desc. 45 ft. over NW. slope.				
37.20	Ravine, drains S. 50° W.; asc. 35 ft. over SW. slope.				
39.97	<p>The 1/4 sec. cor. of secs. 8 and 9, perpetuated and recorded by Arthur Boyer, Deputy Douglas County Surveyor, in 1939, and further perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1958, monu- mented with an iron rod, 3/4 in. diam., firmly set, projecting 2 ins. above ground, from which the remains of an original bearing tree</p> <p style="margin-left: 40px;">A root hole, bears S. 32° W., 13 lks. dist., with a down fir, 15 ins. diam., with fragmentary scribe marks visible on decayed blaze.</p> <p>and a bearing tree mkd. by Boyer</p> <p style="margin-left: 40px;">A fir snag, 50 ins. diam., bears S. 78 1/4° E., 75 1/2 lks. dist., with fragmentary scribe marks visible on bark blaze.</p>				