

County Surveyor's Record, Douglas County, Oregon

17004

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

and bearing trees mkd. by Byron

A cedar, 19 ins. diam., bears S. 25 1/2° E.,
134 lks. dist., with healed blaze.

A white fir, 15 ins. diam., bears S. 40° W.,
73 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 29 S R 8 W
1/4
S 8 S 9
1980

*B.C.
FD OK
8/95
M 119-69
m. Smalley
8/95 M 119-69*

from which new bearing trees

A white fir, 9 ins. diam., bears S. 46 1/2° E.,
5 1/2 lks. dist., mkd. 1/4 S9 BT.

A white fir, 7 ins. diam., bears N. 46° W.,
22 1/2 lks. dist., mkd. 1/4 S8 BT.

N. 0° 03' W., beginning new measurement.

Ascend 40 ft. over SW. slope.

9.85 Spur, slopes W.; desc. 55 ft. over NW. slope.

16.20 Ravine, drains W.; asc. 60 ft. over SW. slope.

16.90 Dirt road, 15 lks. wide, bears E. and W.

20.085 The N 1/16 sec. cor. of secs. 8 and 9, established by
Russell D. Hendricks, Registered Land Surveyor, No. 688,
in 1980, and accepted as a careful and faithful deter-
mination of the position of the cor. monumented with an
iron rod, 1/2 ins diam., firmly set projecting 2 ins.
above ground, from which bearing trees mkd. by Hendricks
in 1980

A white fir, 8 ins. diam., bears N. 57 1/4° E.,
29 lks. dist., with scribe marks N 1/16 S9 BT
visible on open blaze.

A white fir, 10 ins. diam., bears S. 53° W.,
40 1/2 lks. dist., with scribe marks N. 1/16 S8 BT
visible on open blaze.

N. 0° 03' W., beginning new measurement.

Ascend 15 ft. over SW. slope.

3.00 Spur, slopes W.; desc. 25 ft. over NW. slope.

5.65 Ravine, drains S. 55° W.; asc. 120 ft. over SW. slope.

15.85 Gravelled road, 30 lks. wide, bears N. 35° W. and
S. 25° E.

20.085 Point for the cor. of secs. 4, 5, 8 and 9, at propor-
tionate dist.; there is no remaining evidence of the
original cor.