

County Surveyor's Record, Douglas County, Oregon

17005

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.

T 29 S	R 8 W
S 5	S 4
S 8	S 9
1980	

from which

A fir, 9 ins. diam., bears N. 29 3/4° E., 24 lks. dist., mkd. T29S 8W S4 BT.

A fir, 8 ins. diam., bears S. 54 1/2° E., 41 1/2 lks. dist., mkd. T29S R8W S9 BT.

A fir, 11 ins. diam., bears S. 12 1/4° W., 18 lks. dist., mkd. T29S R8W S8 BT.

A fir, 6 ins. diam., bears N. 85 3/4° W., 6 lks. dist., mkd. T29S R8W S5 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, chinquapin, and alder,; undergrowth, salal, Oregon grape, vine maple, rhododendron, poison oak, fern, and grasses.

From the cor. of secs. 3, 4, 9, and 10.

S. 89° 41' W., bet. secs. 4 and 9.

Ascend 350 ft. over NE. slope, through heavy timber and dense undergrowth.

17.60 Ridge, bears N. 30° W. and S. 30° E.; desc. 25 ft. over E. slope.

19.87 Point for the E 1/6 sec. cor. of secs. 4 and 9.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16	S 4
	S 9
1980	

B-
FD
5/93
M117-22

from which

A white fir, 7 ins. diam., bears N. 37° W., 33 lks. dist., mkd. E 1/16 S4 BT.

A grand fir, 12 ins. diam., bears S. 33° E., 13 lks. dist., mkd. E 1/16 S9 BT.

From this point, an iron rod, 3/4 in. diam., firmly set. projecting 14 ins. above ground, not of known record, bears S. 39° E., 0.027 chs. dist.

Descend 105 ft. over SW. slope.

24.35 Creek, 3 lks. wide, course S. 5° W.; asc. 120 ft. over SE. slope.