

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

17006

CHAINS										
29.65	Top of ascent, slopes N.; desc. 50 ft. over broken W. slope.									
38.45	Ravine, drains S. 40° W.; asc. 5 ft. over SE. slope.									
39.74	<p>The 1/4 sec. cor. of secs. 4 and 9, perpetuated and recorded by Arthur Boyer, Deputy Douglas County Surveyor, in 1939, and further perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1958, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 45 ins. diam., bears N. 8° E., 164 lks. dist., with fragmentary scribe marks visible on bark blaze.</p> <p>and a bearing tree mkd. by Boyer</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 10° W., 100 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A sawed fir stump, 10 ins. diam., bears N. 56° W., 32 1/2 lks. dist., with fragmentary scribe marks visible on opened blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">T 29 S</td> <td style="padding-right: 10px;">R 8 W</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">1/4</td> <td style="padding-right: 10px;">S 4</td> <td style="border-top: 1px solid black; border-bottom: 1px solid black; padding: 0 10px;">S 9</td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">1980</td> </tr> </table> </div> <p style="margin-left: 50px;">BC FD OK BY L. 30 5/93 M 11.22</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A white fir, 8 ins. diam., bears N. 22 1/2° E., 65 lks. dist., mkd. 1/4 S4 BT.</p> <p style="padding-left: 40px;">A white fir, 12 ins. diam., bears S. 65 1/2° W., 71 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit the iron rod alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 54' W., beginning new measurement.</p> <p>Ascend 10 ft. over SE. slope.</p>	T 29 S	R 8 W		1/4	S 4	S 9			1980
T 29 S	R 8 W									
1/4	S 4	S 9								
		1980								
2.20	Spur, slopes S. 10° W.; desc. 85 ft. over SW. slope.									
15.15	Ravine, drains S. 10° E.; asc. 30 ft. over SE. slope.									
15.60	Dirt road, 15 lks. wide, bears N. 10° E. and S. 5° W.									
17.65	Gravelled road, 30 lks. wide, bears N. 55° W. and S. 30° E.									
19.895	<p>Point for the W 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>									