

# County Surveyor's Record, Douglas County, Oregon

17007

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

W 1/16  $\frac{S\ 4}{S\ 9}$   
1980

*bc  
BY  
MAY 7 1983*

from which

A fir, 7 ins. diam., bears North, 29 1/2 lks.  
dist., mkd. W 1/16 S4 BT.

A fir, 6 ins. diam., bears S. 38 1/4° E., 5 1/2 lks.  
dist., mkd. W 1/16 S9 BT.

From this point, an iron rod, 3/4 in. diam., firmly set,  
projecting 4 ins. above ground, not of known record,  
bears S. 10° W., 0.040 chs. dist.

Ascend 60 ft. over SE. slope.

23.20 Spur, slopes N. 30° W.; desc. 50 ft. over W. slope.

39.79 The cor. of secs. 4, 5, 8, and 9.

Land, Mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone,  
chinquapin, and alder; undergrowth, salal, rhododendron,  
vine maple, Oregon grape, poison oak, fern, and grasses.

N. 0° 49' W., bet. secs. 4 and 5.

Ascend 10 ft. over SE. slope, through scattering timber  
and dense undergrowth.

2.75 Ridge, bears N. 60° W. and S. 60° E.; desc. 285 ft. over  
NE. slope.

18.00 Creek, 10 lks. wide, course S. 45° W.; asc. 280 ft. over  
broken SW. slope.

18.65 Dirt road, 15 lks. wide, bears E. and S. 45° W.

40.17 The 1/4 sec. cor. of secs. 4 and 5, perpetuated and  
recorded by James W. Byron, Deputy Douglas County  
Surveyor, in 1958, monumented with an iron post, 1 1/4 ins.  
diam., firmly set, projecting 10 ins. above ground, with  
brass cap mkd.

T 29 S    R 8 W  
      1/4  
      S 5 | S 4  
      1958

from which the remains of an original bearing tree

A fir stub, 56 ins. diam., bears S. 70° E.,  
12 lks. dist., with a down log alongside, with  
fragmentary scribe marks visible on bark blaze.

and bearing trees mkd. by Byron

A fir, 18 ins. diam., bears S. 48° E., 103 1/2 lks.  
dist., with healed blaze.

A white fir snag, 11 ins. diam., bears S. 73° W.,  
31 lks. dist., with healed blaze.