

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17008**
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>and new bearing trees</p> <p style="margin-left: 40px;">A white fir, 10 ins. diam., bears S. 84 1/4° E., 8 lks. dist., mkd. 1/4 S4 BT.</p> <p style="margin-left: 40px;">A white fir, 13 ins. diam., bears S. 26 3/4° W., 26 1/2 lks. dist., mkd. 1/4 S5 BT.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, maple, oak, madrone, chinquapin, myrtle, and alder; undergrowth, salal, vine maple, poison oak, rhododendron, Oregon grape, hazel, fern and grasses.</p>
39.80	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>S. 89° 10' W., bet. secs. 5 and 8.</p> <p>Descend 220 ft. over SW. slope, through scattering timber and dense undergrowth.</p> <p>The 1/4 sec. cor. of secs. 5 and 8, reestablished by Russell D. Hendricks, Registered Land Surveyor, No. 688, in 1980, and accepted as a careful and faithful restoration of the position of the cor., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Hendricks.</p> <p style="margin-left: 40px;">A white fir, 5 ins. diam., bears N. 46 1/2° W., 31 1/2 lks. dist., with scribe marks 1/4 S5 BT visible on open blaze.</p> <p style="margin-left: 40px;">A hemlock, 10 ins. diam., bears S. 17 1/2° E., 33 lks. dist., with scribe marks 1/4 S8 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 29 S R 8 W</p> <p>1/4 $\frac{S 5}{S 8}$</p> <p>1980</p> </div> <p>Deposit the iron rod alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 10' W., beginning new measurement.</p> <p>Descend 165 ft. over NW slope.</p>
6.75	Creek, 15 lks. wide, course S.; asc. 105 ft. over SE. slope.
14.20	Top of ascent, slopes S.; desc. 95 ft. over NW. slope.
22.30	Ravine, drains N.60° W.; asc. 10 ft. over NE. slope.
30.35	Spur, slopes S. 80° W.; desc. 60 ft. over broken W. slope.