

County Surveyor's Record, Douglas County, Oregon

17009

Dependent Resurvey, Portion of Subdivisional Lines
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS
39.80

The cor. of secs. 5, 6, 7, and 8, perpetuated and recorded by H. L. Eppstein, Douglas County Surveyor, in 1926, and further perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1958, and accepted as a careful and faithful perpetuation of the position of the original cor., monumented with an iron bar, 1 in. x 1 in., firmly set, projecting 3 ins. above ground, from which a bearing tree mkd. by Eppstein

A fir snag, 36 ins. diam., bears N. 76° E.,
256 1/2 lks. dist., with fragmentary scribe marks
visible on bark blaze.

and bearing trees mkd. by Byron

A fir, 10 ins. diam., bears N. 82° E., 33 lks.
dist., with healed blaze.

A fir, 12 ins. diam., bears S. 56 1/2° W., 55 1/2 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*BOOK
895 M. Smalley
M 119-69*

T 29 S	R 8 W
S 6	S 5
S 7	S 8
1980	

from which new bearing trees

A fir, 10 ins. diam., bears S. 31° E., 46 lks.
dist., mkd. T29S R8W S8 BT.

A fir, 4 ins. diam., bears N. 39° W., 12 1/2 lks.
dist., mkd. X BT.

Deposit the iron bar alongside the iron post.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, chinquapin, and alder; undergrowth, salal, rhododendron, vine maple, Oregon grape, poison oak, hazel, fern, and grasses.

Subdivision of Section 9,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 9 and 16.

N. 0° 04' W., on the N. and S. center line of sec. 9, marking and blazing the true line.

Ascend 15 ft. over SW. slope, through scattering timber and dense undergrowth.

5.55

Top of ascent, slopes W.; desc. 20 ft. over NW. slope.

13.70

Creek, 10 lks. wide, course N. 45° W.; asc. 20 ft. over broken SW. slope.