

County Surveyor's Record, Douglas County, Oregon

17011

Subdivision of Sec. 9,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS										
	<p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>S. 89° 44' W., on the E. and W. center line of sec. 9.</p> <p>Ascend 110 ft. over NE. slope.</p>									
5.45	<p>Spur, slopes N. 5° E.; desc. 15 ft. over SE. slope.</p>									
8.75	<p>Head of ravine, drains N. 10° E.; desc. 70 ft. over NW. slope.</p>									
19.89	<p>Point for the center E 1/16 sec. cor. of sec. 9</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">C</td> <td style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">E 1/16</td> <td style="padding: 0 10px;">C</td> </tr> <tr> <td></td> <td style="text-align: center;">S 9</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1980</td> <td></td> </tr> </table> </div> <div style="position: absolute; top: -40px; right: -100px; transform: rotate(-15deg); font-size: small; font-weight: bold;"> Change Report 05-10-7/13/86 C.S. 63/9 </div> <p>from which</p> <p style="margin-left: 40px;">A white fir, 10 ins. diam., bears N. 1 1/4° E., 47 lks. dist., mkd. CE 1/16 S9 BT.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 4° E., 28 1/2 lks. dist., mkd. CE 1/16 S9 BT.</p> <p>From this point, an iron rod, 3/8 in. diam., firmly set, projecting 2 ins. above ground, not of known record, bears N. 1 1/2° W., 0.036 chs. dist.</p> <p>Descend 10 ft. over NW. slope.</p>	C	E 1/16	C		S 9			1980	
C	E 1/16	C								
	S 9									
	1980									
21.15	<p>Creek, 2 lks. wide, course N. 20° W.; desc. 15 ft. over NW. slope.</p>									
25.00	<p>The NE. cor. of wood frame pumphouse, 15 x 9 ft., bears South, 0.145 chs. dist., long side bears S. 70° W.</p>									
39.78	<p>The center 1/4 sec. cor. of sec. 9.</p> <p>Descend 85 ft. over SW. slope.</p>									
44.95	<p>State Highway No. 42, asphalt paved, 40 lks. wide, bears N. and S.</p>									
58.00	<p>Creek, 1 lk. wide, course S.; desc. 10 ft. over NW. slope.</p>									
59.67	<p>Point for the center W 1/16 sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">C</td> <td style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">W 1/16</td> <td style="padding: 0 10px;">C</td> </tr> <tr> <td></td> <td style="text-align: center;">S 9</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1980</td> <td></td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 69 1/2° E., 42 lks. dist., mkd. CW 1/16 S9 BT.</p> <p style="margin-left: 40px;">A cedar, 15 ins. diam., bears S. 18° E., 42 lks. dist., mkd. CW 1/16 S9 BT.</p>	C	W 1/16	C		S 9			1980	
C	W 1/16	C								
	S 9									
	1980									