

County Surveyor's Record, Douglas County, Oregon

17012

Subdivision of Sec. 9,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

From this point an angle iron, 1 x 1 in., firmly set, projecting 4 ins. above ground, not of known record, bears N. 7 1/2° E., 0.016 chs. dist.

Descend 2 ft. over SW. slope.

63.15 Creek, 1 lk. wide, course S.; asc. 110 ft. over E. slope.

64.70 Dirt road, 15 lks. wide, bears N. and S.

67.70 Ridge, bears N. and S., also dirt road, 25 lks. wide; desc. 60 ft. over NW. slope.

77.55 Ravine, drains S. 50° W.; asc. 10 ft. over SE. slope.

79.56 The 1/4 sec. cor. of secs. 8 and 9.

From the center E 1/16 sec. cor. of sec. 9.

N. 0° 04' W., on the N. and S. center line of the NE 1/4 of sec. 9.

Ascend 25 ft. over broken SW. slope, through heavy timber and dense undergrowth.

6.70 Spur, slopes N. 50° W.; desc. 185 ft. over broken N. slope.

12.95 Creek, 5 lks. wide, course S. 65° E.; asc. 270 ft. over broken SW. slope.

14.60 State Highway No. 42, asphalt paved, 40 lks. wide, bears N. 70° W. and S. 65° E.

28.95 Spur, slopes N. 60° W.; desc. 10 ft. over NW. slope.

30.85 Head of ravine, drains S. 55° W.; asc. 70 ft. over NE. slope.

40.07 The E 1/16 sec. cor. of secs. 4 and 9.

From the E 1/16 sec. cor. of secs. 9 and 16.,

N. 0° 01' W., on the N. and S. center line of the SE 1/4 of sec. 9.

Descend 20 ft. over NW. slope.

0.50 Three-wire power transmission line, bears E. and W.

20.035 Point for the SE 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the SE 1/4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.

SE 1/16 S 9

1980

from which

A white fir, 16 ins. diam., bears N. 43° E.,
22 lks. dist., mkd. SE 1/16 S9 BT.

A fir, 12 ins. diam., bears N. 11° W.,
50 lks. dist., mkd. SE 1/16 S9 BT.