

# County Surveyor's Record, Douglas County, Oregon

**17013**

Subdivision of Sec. 9,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	Descend 50 ft. over NW. slope.
40.07	The center E 1/16 sec. cor. of sec. 9
	From the S 1/16 sec. cor. of secs. 9 and 10.
	S. 89° 46' W., on the E. and W. center line of the SE 1/4 of sec. 9.
	Descend 90 ft. over SW. slope.
19.87	The center S 1/16 sec. cor. of sec. 9,
	Descend 100 ft. over broken SW. slope.
39.74	The center S 1/16 sec. cor. of sec. 9.
	From the W 1/16 sec. cor. of secs. 9 and 16.
	N. 0° 04' E., on the N. and S. center line of the SW 1/4 of sec. 9.
	Descend 5 ft. over N. slope.
0.60	Three-wire power transmission line, bears E. and W.
1.00	Enter swamp, edge bears E. and W.
4.50	Leave swamp, edge bears E. and W.
7.60	Top of ascent, slopes W.; desc. 2 ft. over N. slope.
20.01	Point for the SW 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the SW 1/4.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SW 1/16 S 9 1980
	from which
	A fir, 10 ins. diam., bears S. 3 1/2° E., 34 lks. dist., mkd. SW 1/16 S9 BT.
	A fir, 11 ins. diam., bears N. 65 1/2° W., 23 lks. dist., mkd. SW 1/16 S9 BT.
	Ascend 45 ft. over SW. slope.
39.90	Top of ascent, slopes W.; desc. 5 ft. over N. slope.
40.02	The center W 1/16 sec. cor. of sec. 9.
	From the center S 1/16 sec. cor. of sec. 9.
	S. 89° 50' W., on the E. and W. center line of the SW 1/4 of sec. 9.
	Descend 110 ft. over SW. slope.
5.25	Four-wire power transmission line, bears N. and S.
5.45	State Highway No. 42, asphalt paved, 40 lks. wide, bears N. and S.