

# County Surveyor's Record, Douglas County, Oregon

17014

Subdivision of Sec. 9,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

<p><b>CHAINS</b> 19.935</p>	<p>The SW 1/16 sec. cor. of sec. 9.</p> <p>Descend 10 ft. over SW. slope.</p>
<p>25.75</p>	<p>Creek, 2 lks. wide, course S. 10° W.; asc. 130 ft. over SE. slope.</p>
<p>34.20</p>	<p>Dirt road, 15 lks. wide, bears N. and S.</p>
<p>34.30</p>	<p>Ridge, bears N. and S.; desc. 65 ft. over SW. slope.</p>
<p>39.87</p>	<p>The S 1/16 sec. cor. of secs. 8 and 9.</p>
<p>From the center W 1/16 sec. cor. of sec. 9.</p> <p>N. 0° 05' W., on the N. and S. center line of the NW 1/4 of sec. 9.</p> <p>Ascend 85 ft. over NW. slope.</p>	
<p>18.40</p>	<p>Gravelled road, 30 lks. wide, bears N. 70° W. and S. 50° E.</p>
<p>20.90</p>	<p>Ravine, drains S. 15° W.; asc. 115 ft. over SE. slope.</p>
<p>40.11</p>	<p>The W 1/16 sec. cor. of secs. 4 and 9.</p>
<p>Subdiviison of Section 10 T. 29 S., R. 8 W., Willamette Meridian, Oregon</p>	
<p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 0° 12' E., on the N. and S. center line of sec. 10.</p> <p>Descend 20 ft. over NW. slope, through heavy timber and dense undergrowth.</p>	
<p>5.05</p>	<p>Head of ravine, drains S. 65° W.; asc. 15 ft. over S. slope.</p>
<p>4.90</p>	<p>Spur, slopes S. 70° W.; asc. 5 ft. over SW. slope.</p>
<p>20.02</p>	<p>Point for the center S 1/16 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre style="font-family: monospace; font-size: 1.2em;">           C                 S 1/16   S 10                       C           </pre> </div> <p style="text-align: center;">1980</p> <p>from which</p> <p style="margin-left: 40px;">A grand fir, 11 ins. diam., bears S. 31° E., 21 lks. dist., marked C S 1/16 S10 BT.</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears S. 76 1/2° W., 42 lks. dist., marked C S 1/16 S10 BT.</p> <p>Ascend over SW. slope.</p>