

# County Surveyor's Record, Douglas County, Oregon

**17015**

Subdivision of Sec. 10,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
20.10	Ridge, bears N. 15° W. and S. 10° E.; desc. 515 ft. over NE. slope.
33.70	Dirt road, 15 lks. wide, bears N. 85° W. and S. 85° E.
40.04	Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 29 S R 8 W                      C 1/4 S 10                      1980                 </div> from which  <div style="margin-left: 40px;">                         A fir, 11 ins. diam., bears N. 51 1/2° E., 38 lks. dist., marked C 1/4 S10 BT.                           A fir, 12 ins. diam., bears N. 79 1/2° W., 13 1/2 lks. dist., marked C 1/4 S10 BT.                     </div> Descend 40 ft. over NE. slope.
41.55	Ravine, drains N. 80° E.; asc. 50 ft. over SE. slope.
45.15	Spur, slopes N. 30° E.; desc. 220 ft. over NW. slope.
50.80	Dirt road, 15 lks. wide, bears N. 75° W. and S. 75° E.
51.90	Creek, 1 lk. wide, course N. 45° E.; asc. 10 ft. over SE. slope.
53.45	Spur, slopes N. 60° E.; desc. 205 ft. over NE. slope.
61.45	Shields Creek, 10 lks. wide, course S. 50° E.; asc. 195 ft. over broken S. slope.
65.70	A three-wire power transmission line, bears N. 40° W. and S. 40° E.
66.75	A four-wire power service line, bears N. 55° W. and S. 55° E.
74.75	State Highway No. 42, paved, 50 lks. wide, bears S. 70° W. from S. 75° E., in curve.
80.14	The 1/4 sec. cor. of secs. 3 and 10, perpetuated and recorded by Bruce A. Shaner, Registered Land Surveyor, No. 430, in 1972, monumented with an iron post, 2 1/2 ins. diam. firmly set, projecting 8 ins. above ground, with brass cap mkd.  <div style="text-align: center;">                     T 29 S R 8 W WM                      1/4 <u>S 3</u>                                S 10                      1972                 </div> from which the remains of the original bearing trees  <div style="margin-left: 40px;">                         A root hole, bears N. 66° E., 12 lks. dist.; no tree remains.                           A sawed fir stump, 36 ins. diam., bears S. 64° E., 20 lks. dist., with scribe marks 1/4 S10 visible on open decayed blaze.                     </div>

Cor. Report  
 0540 2/18/84  
 C.S. 63/79