

County Surveyor's Record, Douglas County, Oregon

17016

Subdivision of Sec. 10,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>and new bearing trees</p> <p style="margin-left: 40px;">A cedar, 7 ins. diam., bears N. 61 1/2° E., 46 lks. dist., marked 1/4 S3 BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 39 1/2° W., 47 lks. dist., marked 1/4 S10 BT.</p> <p>From this point, a cor. established by Arthur Boyer, Deputy Douglas County Surveyor, in 1967, by proportionate measurement, bears S. 51 3/4° W., 0.219 chs. dist., monumented with an iron pipe, 1/2 in. diam., inside of an iron pipe, 1 in. diam., firmly set, projecting 18 ins. above ground, from which bearing trees marked by Boyer</p> <p style="margin-left: 40px;">A cedar, 8 ins. diam., bears N. 23° E., 66 lks. dist., with scribe marks 1/4 S3 1581 BT visible on open blaze.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 56° W., 3 lks. dist., with healed double blaze.</p>
	<p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>S. 89° 47' W., on the E. and W. center line of sec. 10.</p> <p>Descend 115 ft. over NW. slope, through heavy timber and dense undergrowth.</p>
4.80	Creek, 2 lks. wide, course N. 20° E.; asc. 245 ft. over E. slope.
9.65	Spur, slopes N. 70° E.; asc. 90 ft. along NE. slope.
17.40	Top of ascent, slopes N.; desc. 20 ft. over NW. slope.
19.82	Point for the center E 1/16 sec. cor. of sec. 10.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $C \frac{E \ 1/16}{S \ 10} C$ <p>1980</p> </div> <p>from which</p> <p style="margin-left: 40px;">A cedar, 7 ins. diam., bears S. 44 3/4° E., 86 lks. dist., marked C E 1/16 S10 BT.</p> <p style="margin-left: 40px;">A grand fir, 10 ins. diam., bears N. 35° W., 26 lks. dist., marked C E 1/16 S10 BT.</p> <p>Descend 65 ft. over NW. slope.</p>
23.25	Ravine, drains N. 55° E.; asc. 250 ft. over E. slope.
27.95	Dirt road, 15 lks. wide, bears N. 15° W. and S. 15° E.
33.25	Spur, slopes N. 10° E.; asc. 25 ft. along N. slope.
36.25	Spur, slopes N.; desc. 30 ft. over NW. slope.
39.64	The center 1/4 sec. cor. of sec. 10.
	Descend 5 ft. over NW. slope.