

County Surveyor's Record, Douglas County, Oregon

17017

Subdivision of Sec. 10,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|---|
| 40.00 | Creek 2 lks. wide, course N. 44° E.; asc. 10 ft. over NE. slope. |
| 41.60 | Ravine, drains N. 25° E.; asc. 200 ft. over SE. slope. |
| 45.50 | Dirt road, 15 lks. wide, bears N. 30° W. and S. 35° E. |
| 50.45 | Spur, slopes N. 60° E.; asc. 5 ft. along broken NE. slope. |
| 56.20 | Top of ascent, slopes N.; desc. 170 ft. over NW. slope. |
| 64.50 | Creek, 4 lks. wide, course N. 5° E.; asc. 105 ft. over NE. slope. |
| 73.95 | Spur, slopes N.; desc. 110 ft. over NW. slope. |
| 79.10 | A three-wire power transmission line, bears N. and S. |
| 79.49 | The 1/4 sec. cor. of secs. 9 and 10. |
| | From the E 1/16 sec. cor. of secs. 10 and 15. |
| | N. 0° 07' E., on the N. and S. center line of the SE 1/4 of sec. 10. |
| | Ascend 90 ft. over SE. slope, through heavy timber and dense undergrowth. |
| 8.80 | Ridge, bears S. 80° E. and S. 60° W.; desc. 165 ft. over NE. slope. |
| 9.75 | Dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E |
| 17.20 | Spur, slopes N. 70° E.; desc. 145 ft. over NE. slope. |
| 20.00 | Point for the SE 1/16 sec. cor. of sec. 10, at intersection with the E. and W. center line of the SE 1/4. |
| | Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | SE 1/16 |
| | S 10 |
| | 1980 |
| | from which |
| | A grand fir, 11 ins. diam., bears N. 87° E., 100 lks. dist., marked SE 1/16 S10 BT. |
| | A grand fir, 14 ins. diam., bears N. 37° W., 48 lks. dist., marked SE 1/16 S10 BT. |
| | Drive a 6 ft. fiberglass fence post alongside the iron post. |
| | Descend 80 ft. over NE. slope. |
| 23.25 | Creek, 5 lks. wide, course N. 35° E.; asc. 10 ft. over SE. slope. |
| 37.40 | Spur, slopes N. 70° E.; desc. 45 ft. over NW. slope. |
| 40.00 | The center E 1/16 sec. cor. of sec. 10. |