

# County Surveyor's Record, Douglas County, Oregon

17018

Subdivision of Sec. 10,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	From the S 1/16 sec. cor. of secs. 10 and 11.
	S. 89° 42' W., on the E. and W. center line of the SE 1/4 of sec. 10.
	Descend 25 ft. over broken NW. slope, through heavy timber and dense undergrowth.
1.40	Ravine, drains N. 20° W.; asc. 20 ft. over NE. slope.
5.55	Spur, slopes N. 30° W.; desc. 70 ft. over NW. slope.
10.55	Creek, 1 lk. wide, course North; asc. 125 ft. over NE. slope.
17.70	Spur, slopes N. 5° E.; asc. 5 ft. over NE. slope.
19.85	The SE 1/16 sec. cor. of sec. 10.
	Ascend 30 ft. over NE. slope.
24.05	Spur, slopes N. 20° E.; desc. 15 ft. over NW. slope.
26.20	Creek, 2 lks. wide, course N. 20° E.; asc. 475 ft. over NE. slope.
32.55	Dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.
36.85	Spur, slopes S. 85° E. from West; asc. 95 ft. along spur top.
39.60	Ridge, bears N. 15° W. and S. 15° E.; desc. over NW. slope.
39.70	The center S 1/16 sec. cor. of sec. 10.

Subdivision of Section 11,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

	From the 1/4 sec. cor. of secs. 11 and 14.
	N. 0° 07' E., on the N. and S. center line of sec. 11.
	Descend 40 ft. over broken NW. slope, through heavy timber and dense undergrowth.
4.25	Ravine, drains S. 70° W.; asc. 140 ft. over SW. slope.
20.00	Point for the center S 1/16 sec. cor. of sec. 11.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	$  \begin{array}{c}  C \\    \\  S\ 1/16 \quad   \quad S\ 11 \\    \\  C  \end{array}  $
	1980
	from which
	A fir, 6 ins. diam., bears S. 1/2° E., 39 lks. dist., marked CS 1/16 S11 BT.