

# County Surveyor's Record, Douglas County, Oregon

17019

Subdivision of Sec. 11,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 5 ins. diam., bears S. 71 1/2° W., 26 lks. dist., marked X BT.</p> <p>Ascend 25 ft. over SW. slope.</p>
22.40	Ridge, bears E. and W.; desc. 70 ft. over N. slope.
31.45	Spur, slopes N. 50° W.; desc. 305 ft. over N. slope.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S    R 8 W C 1/4    S 11 1980</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 56° E., 33 1/2 lks. dist., marked C 1/4 S11 BT.</p> <p style="padding-left: 40px;">A yew, 15 ins. diam., bears N. 82° W., 15 1/2 lks. dist., marked C 1/4 S11 BT.</p> <p>Ascend 5 ft. over NW. slope.</p>
41.60	Spur, slopes N. 30° W.; desc. 430 ft. over NE. slope.
67.35	Shields Creek, 8 lks. wide, course N. 80° E.; asc. 130 ft. over SE. slope.
71.40	State Highway No. 42, paved, 50 lks. wide, bears N. 55° E. and S. 55° W.
79.85	<p>The 1/4 sec. cor. of secs. 2 and 11, perpetuated and recorded by Arthur Boyer, Deputy Douglas County Surveyor, in 1935, further perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1954, further perpetuated and recorded by Herbert L. Northcraft, Registered Land Surveyor, No. 750, in 1970, monumented with an angle iron, 1 1/2 ins. wide, firmly set, projecting 6 ins. above ground, from which remains of the original bearing trees</p> <p style="padding-left: 40px;">A root hole, bears S. 60° W., 64 lks. dist., no tree remains.</p> <p style="padding-left: 40px;">A root hole, bears N. 32° W., 73 lks. dist., no tree remains.</p> <p>and bearing trees marked by Boyer</p> <p style="padding-left: 40px;">A burned oak snag, 20 ins. diam., bears N. 3° E., 170 lks. dist.; no marks visible.</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears S. 18 1/2° W., 195 lks. dist., with scribe mark B visible on decayed blaze, rescribed by Northcraft, with scribe marks 1/4 COR S11 BT visible on open blaze.</p> <p>and bearing trees marked by Byron</p>