

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 15,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

17022

**CHAINS**

40.14

Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 29 S    R 8 W  
          C 1/4  
          S 15  
          1982

from which

A fir, 11 ins. diam., bears S. 28 1/2° W., 34 1/2 lks. dist., mkd. C 1/4 S15 BT.

A fir, 10 ins. diam., bears N. 80° W., 57 lks. dist., mkd. X BT.

Ascend 190 ft. over broken SE. slope.

60.21

Point for the center N 1/16 sec. cor. of sec. 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

          C  
N 1/16 | S 15  
          C  
          1982

from which

A fir, 9 ins. diam., bears S. 89° E., 14 lks. dist., mkd. CN 1/16 S15 BT.

A cedar, 5 ins. diam., bears N. 69 1/2° W., 21 lks. dist., mkd. CN 1/16 S15 BT.

Ascend 400 ft. over SE. slope.

76.10

Spur, slopes S. 10° W.; desc. 10 ft. over W. slope.

80.28

The 1/4 sec. cor. of secs. 10 and 15.

From the 1/4 sec. cor. of secs. 14 and 15.

S. 89° 47' W., on the E. and W. center line of sec. 15.

Descend 25 ft. over broken SW. slope, through heavy timber and dense undergrowth.

7.05

Ravine, drains S. 20° W.; asc. 100 ft. over SE. slope.

14.90

Spur, slopes S. 10° E.; desc. 50 ft. over SW. slope.

19.30

Ravine, drains S. 10° E.; asc. 5 ft. over E. slope.

19.78

Point for the center E 1/16 sec. cor. of sec. 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.