

County Surveyor's Record, Douglas County, Oregon

17023

Subdivision of Sec. 15,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	C $\frac{E\ 1/16}{S\ 15}$ C 1982
	from which A fir, 15 ins. diam., bears N. 56° E., 85 lks. dist., mkd. CE 1/16 S15 BT. A fir, 5 ins. diam., bears S. 45° W., 131 lks. dist., mkd. CE 1/16 S15 BT. Ascend 175 ft. over broken SE. slope.
39.56	The center 1/4 sec. cor. of sec. 15. Ascend 45 ft. over SE. slope.
48.80	Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.
53.35	Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.
67.55	Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.
71.60	Top of ascent, slopes S.; desc. 20 ft. over SW. slope.
72.20	Creek, 10 lks. wide, course S. 45° E.; asc. 140 ft. over NE. slope.
79.25	The 1/4 sec. cor. of secs. 15 and 16.
20.09	From the center E 1/16 sec. cor. of sec. 15. N. 0° 01' W., on the N. and S. center line of the NE 1/4 of sec. 15. Ascend 240 ft. over SW. slope, changing to a SE. slope, through heavy timber and dense undergrowth. Point for the NE 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the NE 1/4. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. <div style="text-align: center;">NE 1/16 S 15</div> from which A cedar, 18 ins. diam., bears S. 58 1/2° E., 35 lks. dist., mkd. NE 1/16 S15 BT. A fir, 18 ins. diam., bears N. 10° W., 3 lks. dist., mkd. NE 1/16 S15 BT. Ascend 65 ft. over SE. slope.
25.80	Spur, slopes S. 70° E.; desc. 20 ft. over NE. slope.
30.60	Ravine, drains S. 60° E.; asc. 105 ft. over SE. slope.
40.18	The E 1/16 sec. cor. of secs. 10 and 15.