

County Surveyor's Record, Douglas County, Oregon

17024

Subdivision of Sec. 15,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

From the N 1/16 sec. cor. of secs. 14 and 15.

S. 89° 45' W., on the E. and W. center line of the NE 1/4 of sec. 15.

Ascend 15 ft. over SE. slope, through heavy timber and dense undergrowth.

3.25 Spur, slopes S.; desc. 25 ft. over SW. slope.

3.85 Creek, 2 lks. wide, course S. 65° E.; asc. 230 ft. over NE. slope.

19.81 The NE 1/16 sec. cor. of sec. 15.

Ascend 125 ft. over SE. slope.

39.65 The center N 1/16 sec. cor. of sec. 15.

From the E 1/16 sec. cor. of secs. 15 and 22.

N. 0° 25' W., on the N. and S. center line of the SE 1/4 of sec. 15.

Ascend 100 ft. over SE. slope, through heavy timber and dense undergrowth.

13.00 Spur, slopes N. 75° E.; desc. 75 ft. over NE. slope.

20.05 Point for the SE 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the SE 1/4.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SE 1/16
S 15
1982

from which

A fir, 22 ins. diam., bears N. 74 1/2° E., 19 lks. dist., mkd. SE 1/16 S15 BT.

A grand fir, 7 ins. diam., bears S. 52° W., 10 1/2 lks. dist., mkd. SE 1/16 S15 BT.

Descend 110 ft. over NE. slope.

25.60 Creek, 10 lks. wide, course E.; asc. 130 ft. over broken SE. slope.

32.40 Dirt road, 20 lks. wide, bears E. and W.

40.11 The center E 1/16 sec. cor. of sec. 15.

From the S 1/16 sec. cor. of secs. 14 and 15.

S. 89° 45' W., on the E. and W. center line of the SE 1/4 of sec. 15.

Ascend 40 ft. over SE. slope, through heavy timber and dense undergrowth.