

# County Surveyor's Record, Douglas County, Oregon

17027

T. 22S., R. 6 W., Willamette Meridian, Oregon

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, Township 22 South, Range 6 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is:

Portions of the subdivisional lines were surveyed by Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, in 1856, and by William H. Byars, U.S. Deputy Surveyor, in 1871.

The survey of the subdivisional lines was completed and a portion of the subdivisional lines was resurveyed by Carl S. Nicklin, U.S. Deputy Surveyor, in 1897.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1073, Oregon, dated July 20, 1981.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations and refer to the true meridian.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original position. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming a closure were measured twice.

The geographic position of the 1/4 section corner of section 28 only, as scaled from the "DRAIN, OREG." topographic map, published by the United States Geological Survey in 1954 is:

Latitude 43° 37.7' N.      Longitude 123° 25.6' W.

The mean magnetic declination is 18° 30' E.

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 22 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the surveys  
by Harvey Gordon and Charles T. Gardner in 1856  
and William H. Byars in 1871, and  
the resurvey and survey by Carl Nicklin in 1897)

Beginning at the 1/4 sec. cor. of sec. 28 only, perpetuated and recorded by Milo Godfrey, Deputy Douglas County Surveyor in 1961, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 22 S    R 6 W  
          | S 28  
W 1/4    | Only  
          1961