

# County Surveyor's Record, Douglas County, Oregon

17029

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 6 W., Willamette Mer., Oregon

CHAINS	
	<p>T 22 S    R 6 W</p> <p style="margin-left: 100px;">S 20   S 21</p> <p style="margin-left: 100px;">            S 28</p> <p style="margin-left: 100px;">1981</p>
	<p>from which new bearing trees</p> <p style="margin-left: 40px;">A white fir, 8 ins. diam., bears N. 41 1/4° E., 62 1/2 lks. dist., mkd. T22S R6W S21 BT.</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears S. 31° E., 11 lks. dist., mkd. T22S R6W S28 BT.</p> <p>Deposit the "T" iron alongside the iron post.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, maple, oak, madrone, alder, chinquapin, and live oak; undergrowth, salal, Oregon grape, vine maple, poison oak, rhododendron, ferns, and grasses.</p>
	<p>N. 1° 15' E., bet. secs. 20 and 21.</p> <p>Ascend 205 ft. over SE. slope, changing to SW. slope, through heavy timber and dense undergrowth.</p>
12.35	Ridge, bears N. 80° E. and S. 80° W.; desc. 570 ft. over broken NW. slope.
31.70	Ravine, N. 40° E.; asc. 195 ft. over SE. slope.
37.49	Point for the 1/4 sec. cor. of sec. 21 only, at proportion- ate dist.; there is no remaining evidence of the original cor.
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 22 S    R 6 W</p> <p style="margin-left: 100px;">            1/4 S 21</p> <p style="margin-left: 100px;">            1981</p>
	<p>from which</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 60° E., 33 1/2 lks. dist., mkd. 1/4 S21 BT.</p> <p style="margin-left: 40px;">A hemlock, 11 ins. diam., bears S. 80 1/4° E., 6 1/2 lks. dist., mkd. 1/4 S21 BT.</p> <p>Ascend 95 ft. over SE. slope.</p>
40.60	Spur, slopes E.; desc. 285 ft. over NW. slope.
45.95	Wet ravine, drains N. 70° E.; asc. 335 ft. over SE. slope.
54.25	Spur, slopes E.; desc. 555 ft. over NE. slope.
67.20	Dry creek, 3 lks. wide, course S. 80° E.; asc. 300 ft. over SE. slope.
74.98	The cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by Milo Godfrey, Deputy Douglas County Surveyor, in 1961, occupied by the remains of the original cor.