

County Surveyor's Record, Douglas County, Oregon

17031

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Mer., Oregon

CHAINS

A fir, 14 ins. diam., bears S. 48° E., 28 1/2 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears N. 28° W., 44 1/2 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22S	R 6 W
S 19	S 20
S 30	S 29
1981	

N. 88° 25' E., bet. secs. 20 and 29.

Descend 90 ft. over NE. slope, through heavy timber and dense undergrowth.

2.15 Head of ravine, drains N.; asc. 10 ft. over NW. slope.

3.10 Spur, slopes N.; desc. 150 ft. over NE. slope.

9.50 Thistleburn Creek, 15 lks. wide, course N. 35° W.; asc. 200 ft. over SW. slope.

15.35 Gravelled road, 30 lks. wide, bears N. 40° W. and S. 40° E.

25.00 Ravine, drains S. 35° W.; asc. 235 ft. over SW. slope.

40.74 The 1/4 sec. cor. of secs. 20 and 29, perpetuated by Wilford N. Haines, Registered land Surveyor, No. 239, during an unrecorded survey, date unknown, monumented with a 3/4 in. "T" shaped iron rod, firmly set, projecting 4 ins. above ground, with an aluminum washer mkd. RLS 239, from which the remains of an original bearing tree

A sawed fir stump, 52 ins. diam., bears S. 60° W., 210 lks. dist., with scribe marks 1/4 SBT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S	R 6 W
1/4 S 20	
S 29	
1981	

from which new bearing trees

A fir, 17 ins. diam., bears N. 63° E., 20 1/2 lks. dist., mkd. 1/4 S20 BT.

A fir, 10 ins. diam., bears S. 60° W., 23 lks. dist., mkd. 1/4 S29 BT.

N. 87° 44' E., beginning new measurement.

Ascend 30 ft. over SW. slope.