

# County Surveyor's Record, Douglas County, Oregon

17036

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

Descend 10 ft. over rock slope.

0.046 The witness cor. to the cor. of secs. 3, 4, 33, and 34, established and recorded by Bruce A. Shaner, Registered Professional Engineer, No. 4906, in 1974, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

WITNESS CORNER

1974	SOUTH 3 FT TO T 26 S	R 8 W
	S 33   S 34	
	S 4   S 3	
	T 27 S	

Descend 10 ft. over NW. slope, through moderate timber and undergrowth.

0.70 Panther Creek, 30 lks. wide, course S. 80° W.; asc. 80 ft. over SW. slope.

2.85 Spur, slopes S. 20° E.; continue ascending 55 ft. over SE. slope.

4.70 Ravine, drains S. 20° E.; asc. 545 ft. over SW. slope.

20.16 Point for the S 1/16 sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16	
S 33   S 34	<i>Fd. 3/90</i>
1981	<i>C.S. 63/27</i>

from which

A fir, 14 ins. diam., bears S. 71 1/4° E., 12 lks. dist., mkd. S 1/16 S34 BT.

A fir, 17 ins. diam., bears S. 26° W., 47 lks. dist., mkd. S 1/16 S33 BT.

The cor. is located on top of ascent, slopes SE.

Descend 115 ft. over NE. slope.

36.65 Creek, 1 lk. wide, course S. 40° E.; asc. 55 ft. over SW. slope.

40.32 The 1/4 sec. cor. of secs. 33 and 34, established by proportionate measurement and recorded by Bruce A. Shaner, Registered Professional Engineer, No. 4906, in 1974, and accepted as the best available evidence of the position of the original cor., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.