

County Surveyor's Record, Douglas County, Oregon

17037

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 26 S R 8 W

$\frac{1}{4}$
 S 33 | S 34
 1974

from which bearing trees mkd. by Shaner

A fir, 19 ins. diam., bears N. 28° E., 7 lks. dist., with illegible scribe marks visible on partially healed blaze.

A fir, 18 ins. diam., bears N. 56° W., 18 lks. dist., with illegible scribe marks visible on partially healed blaze.

—————

N. 0° 11' E., beginning new measurement.

Ascend 175 ft. over SW. slope.

23.98 Callahan Road, graveled surfaced, 25 lks. wide, bears E. and W.

25.95 Ridge, bears N. 85° W., and S. 75° E.; desc. 430 ft. over NE. slope.

37.70 Ravine, drains N. 35° W.; asc. 65 ft. over SW. slope.

40.33 The cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by Marvin C. Ramsey, Registered Land Surveyor, No. 404, in 1959, monumented with an iron pipe, 2 ins. diam., loosely set, projecting 8 ins. above ground, with brass washer marked RS404, on top, from which the remains of the original bearing trees

A decayed fir snag, 23 ins. diam., bears N. 42° E., 57 lks. dist.; no marks remaining.

A decayed fir snag, 35 ins. diam., bears S. 63° E., 60 lks. dist.; no marks remaining.

A decayed fir snag, 45 ins. diam., bears S. 14° W., 141 lks. dist., no marks remaining.
(Record, 134 lks.)

A decayed fir snag, 33 ins. diam., bears N. 31° W., 58 lks. dist.; no marks remaining.

and bearing trees mkd. by Ramsey

A fir, 18 ins. diam., bears N. 12° E., 44 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 72° E., 47 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 62° W., 9 1/2 lks. dist., with illegible scribe marks visible on opened blaze.

A fir, 22 ins. diam., bears N. 10 1/2° W., 63 lks. dist., with healed blaze.

At the corner point