

County Surveyor's Record, Douglas County, Oregon

17041

Dependent Resurvey, Portion of N. Bdy.,
T. 27 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

available evidence of the position of the original cor.,
monumented with an iron post, 1 1/2 ins. diam., firmly set,
projecting 3 ins. above ground, with brass cap mkd.

T 26 S R 8 W W M

1/4 $\frac{S\ 34}{S\ 3}$

T 27 S

1974

from which bearing trees mkd. by Shaner

A fir, 26 ins. diam., bears N. 27° E., 9 lks.
dist., with healed blaze.

A fir, 23 ins. diam., bears S. 8 1/2° E., 24 1/2 lks.
dist., with healed blaze.

From this point, the cor. of secs. 2, 3, 34, and 35,
bears N. 89° 54' E., 40.56 chs. dist., perpetuated and
recorded by Bruce A. Shaner, Registered Professional
Engineer, No. 4906, in 1974, monumented with an iron
post, 1 1/2 ins. diam., with a brass cap firmly set,
projecting 7 ins. above ground, alongside of which is an
iron pipe, 1 1/2 ins. diam., firmly set, projecting 4 ins.
above ground, and a burned wooden post, 4 x 4 ins.
square, firmly set, projecting 36 ins. above ground, with
scribe marks R8 visible on W. face. The brass cap is mkd.

T 26 S R 8 W

$\frac{34\ | \ 35}{3\ | \ 2}$

T 27 S R 8 W

from which the remains of two original bearing trees

A fir stump, 60 ins. diam., bears S. 25° E.,
71 lks. dist., with old axe marks visible on
decayed blaze. (Record, 64 lks.)

A root hole, bears S. 10° W., 44 lks. dist.,
alongside of which is a downed decayed yew,
6 ins. diam., with no marks remaining.

and trees mkd. by person(s) unknown

A fir, 10 ins. diam., bears N. 61° E.,
28 1/2 lks. dist., with healed blaze.

A fir stump, 36 ins. diam., bears S. 81° E.,
57 lks. dist., with healed blaze.

A hemlock snag, 8 ins. diam., bears S. 77° E.,
16 1/2 lks. dist., remarked S2 T27S R8W BT by
Shaner.

A twin madrone, 8 ins. diam., bears S. 87° W.,
26 1/2 lks. dist., with illegible scribe marks
visible on bark blaze.

A fir, 23 ins. diam., bears N. 68° W.,
19 1/2 lks. dist., with healed blaze.