

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy.,  
T. 27 S., R. 8 W., Willamette Meridian, Oregon

17043

CHAINS  
40.56

The 1/4 sec. cor. of secs. 4 and 33, reestablished at proportionate dist. and recorded by Bruce A. Shaner, Registered Professional Engineer, No. 4906, in 1974, and accepted as the best available evidence of the position of the original cor., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T 26 S

1/4  $\frac{S\ 33}{S\ 4}$

T 27 S

from which bearing trees mkd. by Shaner

A fir, 24 ins. diam., bears N. 13° W., 33 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears S. 35° W., 41 lks. dist., with healed blaze.

S. 89° 54' W., beginning new measurement.

Ascend 70 ft. over SE. slope.

8.45 Spur, slopes S.; desc. 220 ft. over SW. slope.

21.95 Creek, 2 lks. wide, course S.; asc. 325 ft. over broken E. slope.

37.25 Spur ridge, bears N. 40° E. and S. 30° W.; also dirt road, 25 lks. wide, bears N. 20° E. and S. 20° W.; desc. 15 ft. over W. slope.

40.56 The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

T 26 S    R 8 W

$\frac{S\ 32}{S\ 5} \mid \frac{S\ 33}{S\ 4}$

T 27 S

1967

from which three bearing trees mkd. by Heydon in 1896

A decayed fir stump, 30 ins. diam., bears N. 20° E., 48 lks. dist., with old axe marks visible on decayed blaze.

A decayed fir snag, 45 ins. diam., bears S. 38° E., 215 lks. dist., with fragmentary scribe marks visible on decayed blaze.

A fir snag, 50 ins. diam., bears S. 61° W., 315 lks. dist., with no marks visible.

and bearing trees mkd. by person(s) unknown

A fir snag, 62 ins. diam., bears N. 10° E., 225 lks. dist., with scribe marks T26 R8 visible on bark blaze.