

# County Surveyor's Record, Douglas County, Oregon

17044

Dependent Resurvey, Portion of N. Bdy.,  
T. 27 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 54 ins. diam., bears S. 84° W.,  
291 lks. dist., with scribe marks T27S R8  
visible on bark blaze.

and bearing trees mkd. by Peterson

A fir, 13 ins. diam., bears N. 38° E., 21 lks.  
dist., with healed blaze.

A fir, 14 ins. diam., bears S. 23° E., 21 lks.  
dist., with healed blaze.

A fir, 19 ins. diam., bears S. 76° W., 24 lks.  
dist., with healed blaze.

A fir, 20 ins. diam., bears N. 38° W., 12 lks.  
dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, alder, maple, madrone, and  
yew; undergrowth, vine maple, ocean spray, Oregon grape,  
hazel, huckleberry, poison oak, salal, and fern.

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 27 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by William P. Heydon in 1896)

Beginning at the cor. of secs. 3, 4, 9, and 10, at  
proportionate distance; there is no remaining evidence of  
the original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in  
the ground, with brass cap mkd.

T 27 S	R 8 W
S 4	S 3
S 9	S 10

1979

from which

A fir, 22 ins. diam., bears N. 47° E., 38 lks.  
dist., mkd. T27S R8W S3 BT.

A fir, 18 ins. diam., bears S. 71° E., 53 lks.  
dist., mkd. T27S R8W S10 BT.

A fir, 18 ins. diam., bears S. 6° W., 33 lks.  
dist., mkd. T27S R8W S9 BT.

A fir, 20 ins. diam., bears N. 51° W., 25 lks.  
dist., mkd. T27S R8W S4 BT.

From this point, the 1/4 sec. cor. of secs. 3 and 4, bears  
N. 1° 04' E., 39.86 chs. dist., perpetuated and recorded  
by Bruce A. Shaner, Registered Professional Engineer  
No. 4906, in 1974, monumented with an iron post, 1 in.  
diam., firmly set, projecting 6 ins. above ground, with  
brass cap mkd.