

County Surveyor's Record, Douglas County, Oregon

17046

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 27 S R 8 W
1/4 S 9 | S 10
1970

from which the remains of an original bearing tree

A fir stump, 42 ins. diam., bears N. 42° E.,
72 lks. dist., with fragmentary scribe marks
visible on an open blaze.

and bearing trees mkd. by Powell

A tan oak, 10 ins. diam., bears N. 3° E., 52 lks.
dist., with healed blaze.

A hemlock, 11 ins. diam., bears S. 88° W., 54 lks.
dist., with healed blaze.

These control lines were fully retraced, and no evidence
of the intervening cors. was found.

N. 87° 48' W., bet. secs. 4 and 9, marking and blazing
the true line.

Descend 130 ft. over NW slope, through scattering timber
and dense undergrowth.

19.90 Head of ravine, drains N.; asc. 70 ft. over NE. slope.

31.40 Spur, slopes N. 10° E.; desc. 90 ft. over NW. slope.

40.98 Point for the 1/4 sec. cor. of secs. 4 and 9, at propor-
tionate dist.; there is no remaining evidence of the
original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 27 S R 8 W
1/4 $\frac{S 4}{S 9}$
1979

from which

A fir, 17 ins. diam., bears N. 27 1/4° W., 25 lks.
dist., mkd. 1/4 S4 BT.

A fir, 13 ins. diam., bears S. 49 3/4° E., 43 lks.
dist., mkd. 1/4 S9 BT.

Descend 10 ft. over NW. slope.

41.50 Bottom of descent, slopes N. 50° W.; asc. 20 ft. over NE.
slope.

45.10 Top of ascent, slopes NW.; desc. 550 ft. over NW. slope.

62.15 Creek, 4 lks. wide, course N. 50° W.; continue descent of
100 ft. over NW. slope.

69.20 Creek, 6 lks. wide, course N. 40° W.; asc. 100 ft. over
NE. slope.