

County Surveyor's Record, Douglas County, Oregon

17047

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 8 W., Willamette Meridian, Oregon

CHAINS							
73.80	Spur, slopes N. 40° W.; desc. 90 ft. over NW. slope.						
77.15	Ravine, drains N. 30° W.; asc. 10 ft. over NE. slope.						
78.45	Spur, slopes N. 35° W.; desc. 210 ft. over NW. slope.						
81.96	<p>The cor. of secs. 4, 5, 8, and 9, determined from the remains of two original bearing trees</p> <p style="margin-left: 40px;">A root hole, bears N. 16° E.; 4 lks. dist., alongside of which is a down and burned cedar, 16 ins. diam., with fragmentary scribe marks visible on burned blaze.</p> <p style="margin-left: 40px;">A root hole, bears N. 62° W., 80 lks. dist., alongside of which is a down and burned cedar, 12 ins. diam., with axe marks visible on burned blaze.</p> <p>and bearing trees mkd. by Weyerhaeuser Timber Company</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears N. 49 1/4° E., 11 lks. dist., with a nail with "W" embossed on its head at the base. Mark this tree T27S R8W S4 BT.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 11 1/4° E., 27 lks. dist., with a nail with "W" embossed on the head at the base. Mark this tree T27S R8W S9 BT.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 59 1/4° W., 15 lks. dist., with a nail with "W" embossed on the head at the base. Mark this tree T27S R8W S8 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 27 S</td> <td style="padding: 0 10px;">R 8 W</td> </tr> <tr> <td style="padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> </table> <p>1979</p> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 66° W., 55 lks. dist., mkd. T27S R8W S5 BT.</p> <p>Land, mountainous. Soil, clay loam. Timber, fir, cedar, hemlock, tan oak, madrone, alder, maple, and yew; undergrowth, vine maple, hazel, arrowwood, huckleberry, salal, Oregon grape, and fern.</p>	T 27 S	R 8 W	S 5	S 4	S 8	S 9
T 27 S	R 8 W						
S 5	S 4						
S 8	S 9						
12.00	<p>N. 0° 51' E., bet. secs. 4 and 5.</p> <p>Descend 390 ft. over NW. slope, through scattering timber and undergrowth.</p> <p>Panther Creek, 12 lks. wide, course S. 40° W.; asc. 250 ft. over SE. slope.</p>						
19.70	Spur, slopes S. 40° E.; desc. 10 ft. over NE. slope.						