

County Surveyor's Record, Douglas County, Oregon

17049

Subdivision of Section 4,
T. 27 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
39.42	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 S R 8 W</p> <p style="text-align: center;">C 1/4 S 4</p> <p style="text-align: center;">1981</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 56 1/2° E., 23 lks. dist., mkd. C1/4 S4 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 2° W., 34 lks. dist., mkd. C1/4 S4 BT.</p> <p>Descend 30 ft. over NW. slope.</p>
40.30	Ravine, drains N. 70° W.; asc. 10 ft. over SW. slope.
42.35	Spur, slopes N. 60° W.; desc. 260 ft. over NW. slope.
51.70	Panther Creek, 25 lks. wide, course S. 30° W.; asc. 465 ft. over SE. slope.
63.70	Foot of cliff, bears NE. and SW.; asc. 115 ft. over rock.
65.15	Top of cliff; continue ascending 340 ft. over SE. slope.
79.56	The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., hereinbefore described.
	<hr style="width: 20%; margin: 0 auto;"/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 88° 20' W., on the E. and W. center line of Sec. 4.</p> <p>Descend 285 ft. over SW. slope, through moderate timber and undergrowth.</p>
14.85	Creek, 3 lks. wide, course N. 20° W.; asc. 165 ft. over NE. slope.
20.60	Top of ascent, slopes NW.; desc. 60 ft.
26.00	Spur, slopes S. 70° W.; continue descent 510 ft. over broken W. slope.
41.35	The center 1/4 sec. cor. of sec. 4.
	Descend 355 ft. over broken W. slope.
46.55	Panther Creek, 25 lks. wide, course S. 30° W.; asc. 400 ft. over SE. slope.
59.55	Spur, slopes S. 10° W.; desc. 50 ft. over SW. slope.
63.30	Bottom of descent, slopes S.; asc. 100 ft. over SE. slope.
68.50	Spur, slopes S. 15° W.; desc. 50 ft. over SW. slope.
70.80	Ravine, drains S. 10° W.; asc. 230 ft. over broken S. slope.